

Safety Equipment Applicable to “VHC” Racing

RFT: OBLIGATORY - FIA Technical List No. 29 & 36 for all cars from Period ...

(except Formula Ford up to Period ... inclusive)

Helmets:

Cars with RFT: Helmets which conform to the FIA Technical Lists No.33 or 41

All other Cars: Helmets which conform to the FIA Technical List No.25

Safety Harnesses (FIA Technical List No.24)

Cars with RFT: Harnesses must be in date and conform to the Norme 88853/98 = 5 straps (letter C...) or 6 straps (letter D....) in contact with the body

All other cars equipped with a Roll Hoop: The minimum requirement is to be in date Norme 8854/98 = 4 straps in contact with the body (letter B...)

Seats:

Cars with RFT: The adapted seat with an RFT Port and conforming to FIA List No:12 and in date. Local reinforcements to the chassis or the shell are authorised.

All other cars T / CT and GT / GTS from Period F: Original seat, or one which conforms to FIA regulations (Car Documentation) Technical List No:12, in date. Local reinforcements to the chassis or shell are authorised.

For Periods J1 and J2 seats conforming to FIA Technical List No:12 and in date.

Fire Extinguisher:

For T / TC / GT / GTS:

Compulsory: 1 Manual Extinguisher in date, conforming to FIA Technical List No:6, attached according to Annex K.

Recommended: 1 Fitted Fire Extinguisher system, with the Pin “Out” or “Armed” and in date, in accordance with FIA Technical List No:16

For Single & Two seaters: 1 Fitted Fire Extinguisher system, with the Pin “Out” or “Armed” and in date, in accordance with FIA Technical List No:16

Clothing:

Compulsory: Racing Overalls and Gloves: Fire Resistant – FIA 8856/2000

Underwear:

Compulsory: Fire Resistant Hood FIA Norme 8856/2000

Compulsory: Underwear (Long Sleeved T Shirt, Long Underwear) in accordance with FIA Norme 8856/2000

Footwear:

Compulsory: Fire Resistant – FIA 8856/2000

Cameras:

Refer to the text as noted in the Rules of “Championnat de France Circuit VHC”

Roll Hoop:

Compulsory: From Period F, see the document “Minima pour Structure de Securite”

Except for FIA or ASN approval, the minimum is: The fixing points of the Roll Hoop must be fixed to reinforcing plates on the structure by 3 x 8mm bolts (2 bolts for the struts). In addition, the fixing points can be welded to reinforce.

FIA approved Roll Hoop Covering:

For T / CT / GT / GTS equipped with a Roll Hoop, including a base frame, which corresponds to K3, the coverings which are in accordance with Technical List No:23 are compulsory.

Windows and Nets:

Windows: If windows are not laminated glass, the use of clear, non coloured film to the side windows and any rooflights is compulsory. The maximum thickness permitted is 100 microns.

Nets: In the case where the car is not fitted with front side windows, the use of Nets fitted to the Rollover is compulsory.

The Nets which are fitted, must possess the following characteristics:

Minimum Webbing size: 19mm

Minimum size of openings: 25 x 25mm

Maximum size of openings: 60 x 60mm.

Cover the opening of the window to the centre of the wheel.